

# PROLASER<sup>®</sup>4

## Traffic Safety LIDAR



### *New* Following Too Close Mode

#### Superior Operation

- Increased targeting range
- Fast acquisition time so you don't miss
- Improved operation through glass
- Certification management and optional expiration lockout

#### Event Data Logging

- Multiple Event Recall
- High capacity internal memory
- Easy export to spreadsheet
- Display lock

#### Easy to Read Displays

- Highly intuitive & customizable user interface
- 4 selectable aiming reticles
- Multiple language support
- TimeTrak™ HUD tracking indicator (option)
- Count-up timer (option)
- Stopwatch or Following Too Close (option)

#### Superior Ergonomics

- Ideally balanced to reduce fatigue
- 30% lighter than traditional LIDAR
- Ruggedized pistol handle with Hogue® grip

#### Versatile Power Options

- 4 x AA Batteries (alkaline or rechargeable)
- 12 VDC in-car adaptor
- USB powered for use (from PC or car)



Simple operation



Following too close



Events log



Bluetooth handle (option)

**Superior targeting**

**No lost measurements**

**3 year warranty\***

\*For USA only, International configurations may vary. Please contact your Account Manager for details.

Kustom Signals Inc. 9652 Loiret Boulevard, Lenexa, KS, 66219, USA.

[www.KustomSignals.com](http://www.KustomSignals.com)

Tel. **800-458-7866**  
**913.492.1400**

# ProLaser<sup>®</sup> 4

## Traffic Safety LIDAR



### Specifications

Laser wavelength:	904 nm +/- 10 nm
Speed accuracy:	+1/-2 mph (+1/-2 km/h, +1/-2 knots) with truncation
Speed range:	10 - 200 mph (16 - 320 km/h, 8 - 174 knots) 0 minimum speed optional
Target range:	10 - 8,000 ft (3 - 2,400 m)
Range accuracy:	±6 inches (±15 cm)
Display resolution:	0.1 ft (0.1 m)
Acquisition time:	0.3 seconds (on qualified targets)
Laser beamwidth:	1 mR horizontal/2.67 mR vertical
Eye safety:	CDRH/FDA Class 1 or 1M IEC60825-1
Battery life:	25+ hours (typical)
Operating temp:	-22°F to 140°F (-30°C to 60°C)
Power input:	4 x AA batteries USB type B 12 VDC adaptor
I/O data port:	USB with high retention connector
Bluetooth	Optional
Profile (H x W x L):	9.8" x 4.3" x 6.3" (25 cm x 11 cm x 16 cm)
Weight (inc. batteries):	2.5 lbs (1.1 kg)
IP67 water and dust proof	
NHTSA Conforming Product List	

### ProLaser 4 Package includes

- Hogue™ Cobblestone over-sleeve grip
- Battery charger
- 8 AA NiMh rechargeable batteries \*
- USB cable and 12 VDC adapter
- 3 year warranty \*
- Hard carry case

### Construction & Environmental

- Rugged, high-impact polycarbonate handle
- Aluminium housing with rubber bumpers
- Poor weather and obstruction mode

### Accessories

- Tripod
- Lockable motorcycle holsters
- Shoulder stock
- Bluetooth® handle and hip printer
- Saddlebag sleeve padded soft case
- 3x HUD magnification
- Online operator training



IP67 Water proof



4 AA batteries



Wireless hip printer



Optional shoulder stock

Hogue™ pistol grip

### Factory Selectable Options


#### Feature Description

#### Factory Selectable Options

Following Too Close Mode	—————	Following Too Close or Stopwatch mode
Recall Events Menu (included)	—————	Disable Event Recall Menu and target measurement storage OR Collect all target measurements and view on rear display (default) OR Recall Marked Events and save select measurements
TimeTrak™	—————	Programmable HUD indicator for elapsed tracking history timer
Count-up timer	—————	Elapsed time since target speed measured (rear display)
Units of Measure Menu	—————	Disable Units Menu - ships with single selected unit of measure (default) includes mph, kph, knots, or fps OR Units menu - selected units of measure - mph/kph; mph/knots; kph/knots or mph/fps
Certification Management & Lockout - (Patent Pending)	—————	Programmable certification date reminder (default) OR Lock-out if certification has expired
Tamper Detection	—————	Electronic tamper detection available



TimeTrak™



Count-up timer

\*For USA only, International configurations may vary. Please contact your Account Manager for details.